



SHERMAN+REILLY®

CP-50 COMPACT SAFETY PULLER

500 LBS. CAPSTAN PULLER FOR INSTALLATION OF SERVICE DROPS

FEATURES

- Reduces risk of installer injury by eliminating hand pulling
- Lightweight – less than 40 lbs.
- Portable and wheeled for easy remote site use
- On-board power from a battery or gasoline-powered drill (sold separately)
- Spuds for adapting to various conduit sizes included



SPECIFICATIONS

Pulling Capacity, rated:	500 lbs. @ 70 fpm
Height, overall, nom.:	39 1/2 in.
Width, overall, nom.:	17 1/2 in.
Depth, overall, nom.:	16 1/2 in.
Weight*, nom.:	39 lbs.
Frame Material:	Aluminum
Tires:	4.10/3.50-4, pneumatic
Spud Adapter Sizes, ID:	2 in., 2.5 in., 3 in., and 4 in., conduit end
Drill Compatibility:	Compatible with most commonly used gas powered drills

OPTIONS

Battery powered drill adapter kit with flush mount adapter

UD-50 UNDERGROUND PULLER

5,000 LBS. PULLING CAPACITY

FEATURES

- Most cost-effective underground puller
- Compact and rugged for remote jobsites
- Rope entry at a fixed point for better anchorage
- Even, constant pulling force
- Equipped with a tension dynamometer and adjustable overload cut-off
- Available as Pad Mount Transformer Adapter with A-Frame (as pictured) or skid mounted



A-FRAME VERSION

SPECIFICATIONS

Engine:	9.5 Hp gasoline
Fuel Capacity:	1.9 gallon
Pulling Rope:	3/8 in. dia. Steel Cable
Reel Capacity:	1,500 ft. (3/8 in. dia.)
Skid Frame Construction:	Steel tubing, continuous-weld
Instrumentation:	Dial-type Dynamometer w/Load Limiting Device
Wheel Configuration & Tires:	14 x 5.5 Drop Center; ST205-75R 14BC
Brakes, trailer:	Electric, Standard; Hydraulic Surge, Optional
Parking Brake, trailer:	Manual
Electrical System:	12V

Front/Nose Jack:	Screw Type with Wheel
Rear Jacks:	Screw Type with Shoe
Tool Box:	Steel
Trailer Hitch:	Pintle Eye
Width, overall, approx.:	63 in.
Length, overall, approx.:	91 in.
Frame Construction, trailer:	Steel Tubing
Height, approx.:	48 in.
Weight*, approx.:	1,200 lbs.

OPTIONS

- Air Adapter Kits
- Underground Blocks Available